

Granville FS-M 5W/30

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville FS-M 5W/30 is an advanced fully synthetic engine oil formulated from quality base oils and the most up to date additives meeting low SAPS (sulphated ash, phosphorus and sulphur) requirements. It provides excellent wear protection and is safe for use in vehicles that have a diesel particulate filter fitted. Manufactured to meet ACEA C1 specification.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C1

JASO: DL-1

Ford: WSS-M2C934-B

STJLR: .03.5005

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep upright and sealed in a cool, dry place out of the reach of children.



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|----------|---------|---------------|
| 1 Litre | 0697 | 5020618006978 |
| 5 Litre | 0698 | 5020618006985 |
| 20 Litre | 0710 | 5020618007104 |



Granville FS-M 5W/30

1 Litre, 5 Litre & 20 Litre

SHELF LIFE

5 years from date of manufacture.

| | |
|--------------------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |
| Percentage of Biodiesel | : Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|------------------------------|------------|--------------------|------|-------|---------|
| Kinematic Viscosity at 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 10.22 |
| Cold Cranking Viscosity | ASTM D4684 | mPa.s | | 6600 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 6 | | 8.46 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 2.9 | | |
| NOACK Volatility | ASTM D5800 | % | | 13 | |
| Kinematic Viscosity at 40°C | ASTM D445 | mm ² /s | | | 59.59 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

